

PRODUCT DATA SHEET

Racers spectacle



COMPONENTS	MATERIALS	FEATURES	MATERIALS
Lens	Polycarbonate	Temple	Nylon
Frame	Nylon	Soft Temple Tip	PVC
Nose piece	Bridge –Bronze	Hinge	Nylon
	Nose Pad – PVC	Screw	Stainless Steel
	Screw – Stainless Steel		

WEIGHT: 31 g

FEATURES

- Dynamic frame design, available in black or with silver/red surface finish combined with a stylish red rainbow mirror lens
- Very high impact resistant single lens compliant to Military Standards MIL-V-43511C clause 3.5.10. and MIL-PRF-31013 clause 3.5.1.1 (198 m/s)
- Formable wire temples adapt to different head sizes and provide a comfortable fit
- Adjustable soft nose buds for perfect fit also on different nose shapes
- Sightgard coating: MSAs popular anti-fog coating with good anti-scratch properties
- UV Filter 99.9%, light gold mirror lens with UV Filter 100%

ORDERING INFO

10104614 Racers, clear lens, Sightgard (12 pcs)
 10104615 Racers, amber lens, Sightgard (12 pcs)
 10104617 Racers, smoke lens, Sightgard (12 pcs)
 10104618 Racers, red rainbow mirror lens, Sightgard (12 pcs)
 10104616 Racers, light gold mirror lens, UV400, Sightgard (12 pcs)
 All come with a soft bag and cord

MARKINGS/APPROVALS

- Standard Number: **EN166**
Clear lens: 2C-1,2 MSA 1 FT CE
 2C: Ultra violet radiation with enhanced colour recognition
 1,2 Filter; Luminous transmittance ~89%; 99.9% UV filter
 Applications: general use, all indoor applications
Amber lens: 2-1,2 MSA 1 FT CE
 2: Ultra violet radiation
 1,2 Filter; Luminous transmittance ~84%; 99.9% UV filter
 Applications: Contrast enhancement (quality inspection), low light environments
Smoke lens: 5-2,5 MSA 1 FT CE
 5: Sunglare filter without infrared specification
 2,5 Filter; Luminous transmittance ~21%; 99.9% UV filter
 Applications: Most popular sun glare filter
Red rainbow mirror lens: 5-3,1 MSA 1 FT CE
 5: Sunglare filter without infrared specification
 3,1 Filter; Luminous transmittance ~14%; 99.9% UV filter
 Applications: Strong and stylish antiglare filter
Light gold mirror lens: 5-1,7 MSA 1 FT CE
 5: Sunglare filter without infrared specification
 1,7 Filter; Luminous transmittance ~50%; UV 400, 100% filter
 Applications: Changing light conditions, driving, premium UV filter

- Optical class: **1** (best class, for permanent wear)
 - Mechanical resistance: **F** (low energy impact 45 m/s)
 - Additional resistance at extreme temperatures (-5 and 55 °C): **T**
Frame: MSA EN 166 FT

PACKAGING

1 spectacle with a soft bag and cord in a polybag with the manual and an EAN code as barcode

12 spectacles / carton with a special EAN code
 Transportbox contains 12 cartons, has a special EAN code