



542AA2MR2





Hi-vis polo shirt with ARC protection

This stylish arc class one long-sleeved polo shirt protects you against industrial hazards such as arc flashover. The welded and segmented reflective strips are very light and supple, so you are better protected in darker surroundings. This flame retardant and anti-static polo shirt has good moisture-regulating and anti-static properties. Moreover, the Ardva is stylishly finished with a turnover collar and sleeve ends in a contrasting colour.











Hi-vis polo shirt with ARC protection

Ardva - 542AA2MR2

European Standards:

- » IEC 61482-2 : 2009 class 1 EBT 7.4 cal/cm²
- » EN ISO 11612: 2008 / A1 B1 C1 F1
- » EN ISO 14116: 2008 / Index 3/5H/40
- » EN 1149-5 : 2008
- » EN ISO 20471: 2013 / Class 2
- » EN ISO 13688: 2013

Exterior:

- » Lay-flat collar
- » Closure with hidden buttons under flap
- » Long sleeves
- » Welded, segmented reflective tape

54,5% modacrylic + 44,5% cotton + 1% AST; ± 220 g/m²

Sizes:

S - XXXL

Colour:

» 278 Hi-Vis Yellow/Navy

Packaging:

10 pieces per box

Wash and care instructions:











SIOEN head office

Fabriekstraat 23 B-8850 Ardooie Belgium T: +32 (51) 740 800 F: +32 (51) 740 962 www.sioen-ppc.com



Discover our products © 2020 Sioen Apparel - Protection through Innovation, Flexothane®, Siopor® and the SIOEN logo are trademarks of the Sioen Industries Group.

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice.

All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that Sioen disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.